



SAFETY WITHOUT COMPROMISE – GEZE IQ LOCKS
SELF-LOCKING PANIC LOCKS



CONTENTS

Safety without compromise with GEZE IQ locks	4
GEZE IQ locks overview table	4
The advantages of the IQ lock range at a glance	5
GEZE panic bar	5
GEZE IQ locks for 1-leaf doors	
GEZE IQ lock EL - motor lock	6
GEZE IQ lock EM - electromechanical lever lock	8
GEZE IQ lock C - mechanical contact lock	9
GEZE IQ lock M - mechanical lock	10
GEZE IQ lock for doors automated on both sides	
GEZE IQ lock AUT - motor lock	11
GEZE IQ locks for 2-leaf doors	
GEZE IQ lock EL DL - motor lock	12
GEZE IQ lock EM DL - electromechanical lever lock	12
GEZE IQ lock C DL - mechanical contact lock	13
GEZE IQ lock M DL - mechanical lock	13

Safety without compromise with GEZE IQ locks

In an emergency it is necessary to leave a building within seconds, particularly when people are in danger. On the other hand, sensitive areas have to be protected from unauthorised entry. Self-locking panic locks provide uncompromising safety and security for both people and property. With the IQ lock range GEZE has developed optimum solutions for your individual security and safety requirements. Not just for emergency exit routes because the clever lock actually thinks for itself!

Proven safety deserves your trust

Strict standards and guidelines specify the requirements for locks on emergency exit routes. In an emergency, everyone must be able to rely on tested and certified safety. For this reason, GEZE IQ locks are tested according to the standards DIN EN 179, 1125, 12209, 1634-1 and VdS relevant to locks. At the same time, the certificate of compliance assures constant monitoring and control and ensures consistently high quality.

Unique technology for your building too

The innovative cross latch technology of the IQ locks prevents the bolt from blocking even under side loads. The robust and yet precise mechanism enables each person to leave the building safely at any time. With the unique technology of the IQ lock EL DL GEZE now provides the solution for double-leaf full panic doors. With the self-locking panic lock „IQ lock AUT“, GEZE is offering yet another milestone in innovative lock technology. The building management system specialist was the first provider to motorise the passive leaf of 2-leaf doors. Access for all, regulated access control or emergency exit routes in case of danger with reliable smoke and heat extraction (RWA). IQ lock AUT offers a suitable solution for every case.

Integrated security in the GEZE SecuLogic system

A system is more than just a sum of its components. GEZE integrates its products in system solutions for doors on emergency exit routes. The IQ locks can be integrated seamlessly into the GEZE SecuLogic building system and supplement emergency exit systems (RWS) and access control. The advantages of the jam-free bolt of the IQ lock EL also apply in conjunction with GEZE swing door drives. This means maximum functional reliability for the door. GEZE even has an intelligent solution to offer in combination with fresh air supply systems for smoke and heat extraction.

With the IQ lock range, GEZE provides optimum solutions for all individual safety and security requirements, not only in emergency exit routes.

GEZE IQ locks overview table

Characteristics	1-leaf				2-leaf				
	IQ lock EL	IQ lock EM	IQ lock C	IQ lock M	IQ lock AUT	IQ lock EL DL	IQ lock EM DL	IQ lock C DL	IQ lock M DL
Motor-driven unlocking	•				GF, SF	GF			
Mechanical self-locking	•	•	•	•	GF, SF	GF, SF	GF, SF	GF, SF	GF, SF
Full panic					•	•	•	•	•
Divided cross latch (3 mm gap between latch and bolt prevents forcing)	•	•	•	•	GF	GF	GF	GF	GF
Mechanical timeout function / protection from manipulation		•	•	•			•	•	•
Electrical timeout function	•				GF	GF			
Operating mode „secured by day“	•				GF	GF			
Operating mode „permanently unlocked“	•				GF, SF	GF			
Operating mode „night“	•				GF, SF	GF			
Outside handle, can be electrically engaged		•					GF		
Feedback contacts for lock states	•	•	•		GF, SF	GF	GF	GF	

- = Yes
- GF = Active leaf
- SF = Passive leaf

The advantages of the IQ lock range at a glance

Reliable protection against burglary, fast opening in an emergency and controlled access are the strengths of GEZE's self-locking panic locks. Wherever secure locking is required to protect against unauthorised access from the outside, yet at the same time fast evacuation must be guaranteed in an emergency, the IQ lock EL, EM, C and M locks are used. The self-locking mechanism with a bolt projection of 20 mm fulfils the requirements for locking in compliance with the insurance requirements. Controlled opening from the outside is also possible with a key at any time.

Absolutely jam-free bolt ensures reliable opening in an emergency

Thanks to a unique design, the latch protects the bolt against side loads. The narrow gap of 3 mm between the divided cross latches and the bolt prevents the bolt from jamming even if the door is warped. With the help of the panic function E, even locked doors can be opened in the emergency exit direction by pressing the lever handle or the panic bar. When this happens, latch and bolt are pulled back at the same time.

Protection from misuse and incorrect operation

Inadvertent incorrect operation or manipulation by actuating the auxiliary latch is no problem for GEZE's IQ locks. The mechanical or electrical timeout functions prevent the bolt from closing prematurely if the door is open.

Universal use

Regardless of their function, all locks have minimum housing dimensions (165 x 15.2 x backset +15.5 mm). One GEZE IQ lock variant can therefore be conveniently exchanged with another. This means that building users can respond easily and flexibly to changes in requirements.

GEZE panic bar

Horizontal bar made of stainless steel for every application

The GEZE panic bar is the optimum addition to GEZE IQ locks. This horizontal panic lock fulfils the European standard EN 1125 regarding the easy opening of emergency exits.

Important: Panic and emergency exit locks are always made up of a lock and a fitting, these must always be tested and certified together. If the lock and fitting are supplied separately (not within the GEZE scope of delivery) you should remember that only tested, certified and marked products may be used on emergency exits.

Panic bar



Application range

- Exit doors in accordance with DIN EN 1125
- Emergency exits

GEZE IQ lock EL

The motor lock for single-leaf doors

The outstanding features of the electronic motor lock IQ lock EL are its motorised unlocking in less than one second and complete monitoring of the door due to integrated contacts. The GEZE cross latch design and the associated, absolutely jam-free retraction and throw of the bolt reduces the load on the electromechanical components. An advantage that especially predestines the IQ lock EL for combination with swing door drives.



IQ lock EL



Application range

- Doors along emergency exit routes
- Fire protection doors
- Emergency exits
- Access control / emergency exit systems
- Use with GEZE automatic swing door systems
- RWA fresh air

Technical data

Product features	IQ lock EL
DIN direction	left/right
Temperature range	-10 – 50 °C
Motor-driven unlocking	< 1 s
Panic function / mechanical self-locking	•
Divided cross latch (3 mm gap between latch and bolt)	•
Electrical timeout function	•
Three operating modes (secured by day / permanently unlocked / night)	•
Feedback contacts for lock states	•
Optional sabotage monitoring or cylinder contact	•
Operating voltage	12 V, 24 V
Current consumption	80 mA at 24 V / 250 mA at 24 V for a short time, 160 mA at 12 V / 500 mA at 12 V for a short time
Contact rating	30 V / 500 mA
Resistant to forcing	10,000 N
Length of connection cable between lock and control (max.)	10 m

• = YES

Motor lock - control

Inputs connected to potential and control

- Voltage supply 12/24 V DC
- Release
- Day/night
- Smoke detector/fire alarm system
- Door contact for timeout function

Potential-free outputs

- Lever handle actuated
- Bolt extended
- Day/night
- Fault/power failure
- Open/closed door mode
- Sabotage/cylinder contact
- Release

Electrical data

Operating voltage: 24 V / 12 V DC

Current consumption: 150 mA, short-term 250 mA

Load capability of the relay: 30 V / 1 A

Technical data

Dimensions: 139 x 119 x 70 mm (surface-mounted housing)

Enclosure rating: IP 55

Ambient temperature: 0 – 50 °C

Three operating modes for every situation

A high degree of functionality is a basic requirement for flexible design and use options. Here the IQ lock EL offers three different operating modes.

Night

In „night-time operation“ each time the door is closed the automatic bolt projection is 20 mm. Controlled access is ensured, for example, with GEZE SecuLogic access control. In this case, the bolt is retracted and the door can be passed through against the emergency exit direction.

Secured by day with electric strike function

In this mode the bolt remains retracted. The locked cross latch only is responsible for the closed state of the door. This unique function makes the electric strike superfluous. The door opening times are just as fast as if an electric strike was installed. Especially in combination with a GEZE swing door drive the IQ lock EL ensures convenient passing through the door.

Permanently unlocked

In „permanently unlocked“ mode the bolt is completely retracted and the cross latch is not locked – the door can be opened from both sides with no resistance.

Contacts

All contacts required for monitoring the door are integrated in the IQ lock EL and therefore enable complete monitoring of the door. The cylinder, follower, bolt and auxiliary bolt contacts can be analysed as potential-free status inputs and forwarded to monitoring systems. The cylinder contact provides a further positive aspect: combined with the GEZE SecuLogic emergency exit system (RWS) it enables the RWS door control unit to be activated, so that the key operated button becomes redundant in the RWS system and a 1-box solution can be implemented.

Input for fire alarm systems

Irrespective of its current state, if triggered by fire alarm systems or in the event of a power failure the IQ lock EL switches to „night“ mode and is securely locked. All necessary requirements for fire section doors in accordance with EN 1634-1 are therefore fulfilled. Due to successful fire tests the lock can therefore also be used in fire protection doors.

Supplied by GEZE (Set)

- GEZE IQ lock EL
- Motor lock control unit
- Strike plate
- Open door loop
- Power supply cable 10 m
- Universal reed contact
- Optional: power supply unit in surface-mounted housing
- Optional: fitting in accordance with DIN EN 1125
- Optional: concealed door loop

GEZE IQ lock EM

The electromechanical lever lock for single-leaf doors

The electromechanical lever lock IQ lock EM is ideally suited for combination with access control systems. While the panic function exists in the emergency exit direction the outside handle is decoupled from the lock mechanism. An electrical signal emitted by an access control system enables the outside handle to be coupled for a specific period of time or permanently, therefore allowing the door to be opened against the emergency exit direction. Just like with the IQ lock EL, the IQ lock EM can also analyse the cylinder, follower, bolt and auxiliary bolt contacts and use them as potential-free status inputs.



IQ lock EM



Application range

- Doors along emergency exit routes
- Fire protection doors
- Emergency exits
- Access control / emergency exit systems

Technical data

Product features	IQ lock EM
DIN direction	left/right
Temperature range	-10 – 50 °C
Panic function / mechanical self-locking	•
Divided cross latch (3 mm gap between latch and bolt)	•
Mechanical timeout function	•
Outside handle, can be electrically coupled	•
Feedback contacts for lock states	•
Optional sabotage monitoring or cylinder contact	•
Operating voltage	12 V, 24 V, 48 V
Current consumption	350 mA at 12 V, 210 mA at 24 V, 105 mA at 48 V
Contact rating	30 V / 500 mA
Resistant to forcing	10,000 N
Length of connection cable between lock and control (max.)	10 m

• = YES

Supplied by GEZE (Set)

- GEZE IQ lock EM
- Strike plate
- Power supply cable 10 m
- Optional: power supply unit in surface-mounted housing
- Optional: fitting in accordance with DIN EN 1125
- Optional: concealed door loop

GEZE IQ lock C

The mechanical contact lock for single-leaf doors

The contact lock IQ lock C is ideally suited for activating secured emergency exits along escape routes with closing from the outside, i.e. an additional key push button is not necessary. The IQ lock C combines the features of a mechanical panic lock and a lever lock. In terms of functionality, it is a mechanical panic lock with a lever handle on the inside and a door knob on the outside. Analysis via potential-free contacts and forwarding to a monitoring system takes place via cylinder, follower, bolt and auxiliary bolt contacts. An integrated cylinder contact makes a one box solution possible for escape route systems.



IQ lock C



Application range

- Doors along emergency exit routes
- Fire protection doors
- Emergency exits
- Emergency exit system

Technical data

Product features	IQ lock C
DIN direction	left/right
Temperature range	-10 – 50 °C
Panic function / mechanical self-locking	•
Divided cross latch (3 mm gap between latch and bolt)	•
Mechanical timeout function	•
Feedback contacts for lock states	•
Optional sabotage monitoring or cylinder contact	•
Contact rating	30 V / 500 mA
Resistant to forcing	10,000 N
Length of connection cable between lock and control (max.)	10 m

• = YES

Supplied by GEZE (Set)

- GEZE IQ lock C
- Optional: strike plate
- Optional: connection cable
- Optional: fitting in accordance with EN 1125

GEZE IQ lock M

The mechanical lock for single-leaf doors

Purely mechanical locks, in particular, are frequently equipped with electronic knob cylinders. This may sometimes be a problem with regards to panic locks. Since knob cylinders are often not equipped with a cam positioning device it may come to an obstruction of the latch retention at the cam. As a result the door cannot be opened in case of emergency. The IQ lock M is quite different: the sophisticated construction, the small rear backset and the small dimensions of the lock case prevent a collision of cam and latch retention when the door is opened.



IQ lock M



Application range

- Doors along emergency exit routes
- Fire protection doors
- Emergency exits
- Use with GEZE door technology products

Technical data

Product features	IQ lock M
DIN direction	left/right
Temperature range	-10 – 50 °C
Panic function / mechanical self-locking	•
Divided cross latch (3 mm gap between latch and bolt)	•
Mechanical timeout function	•
Resistant to forcing	10000 N

• = YES

Supplied by GEZE (Set)

- GEZE IQ lock M
- Optional: fitting in accordance with DIN EN 1125
- Optional: strike plate

GEZE IQ lock AUT

System solution for double-leaf full panic doors

IQ lock AUT is a multifunctional system solution for full panic doors with door leaves automated on both sides. This means that both active and passive leaves can be unlocked by a motor drive. Thanks to the full panic function, both door leaves can be unlocked mechanically at the same time in an emergency by pressing the panic bar. After passage through the door, the mechanical self-locking feature becomes active, locking both door leaves quickly and securely in line with insurance requirements. As an RWA fresh air system, the IQ lock AUT guarantees the automatic unlocking of both door leaves after automatic release e.g. by means of a smoke detector. This ensures both smoke removal and a convenient exit from the building. The operating mode „permanently unlocked“ allows both locks to be permanently unlocked so that the swing door drives can be activated very quickly by the respective actuation devices, e.g. a radar detector or access control system, allowing fast and safe passage through both door leaves. IQ AUT can easily be fitted to existing doors with the IQ lock EL DL.



On the left: motor lock IQ lock EL DL, centre: strike box DL, on the right: bar drive IQ AUT

Application range

- Doors along emergency exit routes
- 2-leaf full panic function with door leaves automated on both sides
- Fire protection doors
- Emergency exits
- Access control / emergency exit systems
- Use with GEZE automatic swing door systems
- RWA fresh air

Technical data

Product features	IQ lock AUT
DIN direction	left/right
Locking points	2
Temperature range	-20 – 60 °C
Panic function / mechanical self-locking	•
Feedback contacts for lock states	•
Operating voltage	24 V
Actuation	external contact
Current consumption	60 mA at 24 V; max. 1.5 A at 24 V
Length of connection cable between lock and control (max.)	10 m

• = YES


GEZE IQ lock EL DL

The motor lock for double-leaf doors

When the passive leaf is actuated, the active leaf is also opened and enables the whole escape route width to be used. After passing through the door the self-locking mechanism ensures that the door is locked again in line with insurance requirements. The contacts enable problem-free transmission of signals via a fire or other alarm system. This ensures that each opening of the door is registered, including in emergencies or misuse. The system solution for double-leaf doors can therefore be monitored and controlled at all times. Free passage through the door in the direction of escape is ensured at all times.

As well as the mechanical strike box, all the components required for full panic door function are included in the set. A configurable number ensures that the right components are always put together for the respective door.

The IQ lock EL DL for the active leaf has the same functions and advantages as the IQ lock EL.



The technical data corresponds to the 1-leaf variant.

GEZE IQ lock EM DL

The electromechanical lever lock for double-leaf doors

This electromechanical solution is optimum for use on double-leaf full panic doors and for combination with GEZE access control systems.

As well as the mechanical strike box, all the components required for full panic door function are included in the set. A configurable number ensures that the right components are always put together for the respective door.

The IQ lock EM DL for the active leaf has the same functions and advantages as the IQ lock EM.



The technical data corresponds to the 1-leaf variant.

GEZE IQ lock C DL

The mechanical contact lock for double-leaf doors

This solution for double-leaf doors – IQ lock C DL is ideally suited for activating secured emergency exits with closing from the outside, i.e. an additional key switch is not necessary.

As well as the mechanical strike box, all the components required for full panic door function are included in the set. A configurable number ensures that the right components are always put together for the respective door.

The IQ lock C DL for the active leaf has the same functions and advantages as the IQ lock C.



The technical data corresponds to the 1-leaf variant.

GEZE IQ lock M DL

The mechanical lock for double-leaf doors

The GEZE IQ lock M DL is a simple and reliable panic lock for securing double-leaf full panic doors.

As well as the mechanical strike box, all the components required for the full panic door function are included in the set. A configurable number ensures that the right components are always put together for the respective door.

The IQ lock M DL for the active leaf has the same functions and advantages as the IQ lock M.




The technical data corresponds to the 1-leaf variant.

POTENTIAL APPLICATIONS OF GEZE PRODUCTS

You will find more product information in the relevant brochures, see ID numbers.

Door technology	
01	Overhead door closers ID 091593, ID 091594
02	Hold-open systems ID 091593, ID 091594
03	Integrated door closers ID 091609
04	Floor springs and all-glass fittings ID 091607
05	Sliding fitting systems and linear guides ID 123605, ID 000586
Automatic door systems	
06	Swing doors ID 144785
07	Sliding, telescopic and folding doors ID 143639
08	Curved sliding doors ID 135772
09	Revolving doors ID 132050
10	Activation devices and sensors ID 142655
Smoke and heat extraction and window technology	
11	Fanlight opening systems ID 127787
12	Electric opening and locking systems ID 127785, ID 127789
13	Electrical spindle and linear drives ID 127785, ID 127789
14	Electric chain drives ID 127785, ID 127789
15	Smoke and heat extraction systems ID 127785, ID 139075
Safety technology	
16	Emergency exit systems ID 132408
17	Access control systems ID 132158
18	Panic locks ID 132848
19	Electric strikes ID 148666
20	Building management system ID 132408
Glass systems	
21	Manual sliding wall systems (MSW) ID 104377
22	Integrated all-glass systems (IGG) ID 104366



POTENTIAL APPLICATIONS OF GEZE PRODUCTS



Door technology

The functionality, superior performance and reliability of GEZE door closers are impressive. A common design across the range, the ability to use them on all common door leaf widths and weights, and the fact that they can be individually adjusted makes their selection simple. They are continually being improved and enhanced with up-to-date features. For example, the requirements of fire protection and accessibility are fulfilled with a door closer system.

Automatic door systems

GEZE automatic door systems open up a huge variety of options in door design. The latest, innovative high-performance drive technology, safety, ease of accessibility and first class universal drive design set them apart. GEZE offers complete solutions for individual requirements.

Smoke and heat extraction and window technology

GEZE smoke and heat extraction systems and ventilation technology provide complete systems solutions combining the many requirements of different types of windows. We supply a full range from energy efficient drive systems to natural ventilation and complete solutions for supplying and extracting air, also as certified SHEVs.

Safety technology

GEZE safety technology sets the standards where preventative fire protection, access control and anti-theft security in emergency exits are concerned. For each of these objectives GEZE offers tailored solutions, which combine the individual safety requirements in one intelligent system and close doors and windows in case of danger in a coordinated manner.

Building systems

In GEZE's Building Management System GEZE door, window and safety products can be integrated in to the security and control systems of the building. A central control and visualisation system monitors various automation components in the building and offers security through many different networking capabilities.

Glass systems

GEZE glass systems stand for open and transparent interior design. They can either blend discreetly into the architecture of the building or stand out as an accentuated feature. GEZE offers a wide variety of technologies for functional, reliable and aesthetic sliding wall or sliding door systems providing security with lots of design scope.

GEZE GmbH
P.O. Box 1363
71226 Leonberg
Germany

GEZE GmbH
Reinhold-Vöster-Straße 21-29
71229 Leonberg
Germany
Telefon +49 7152 203 0
Telefax +49 7152 203 310
www.geze.com

Germany
 GEZE GmbH
 Niederlassung Süd-West
 Breitwiesenstraße 8
 71229 Leonberg
 Tel. +49 7152 203 594
 Fax +49 7152 203 438
 leonberg.de@geze.com

GEZE GmbH
 Niederlassung Süd-Ost
 Parking 17
 85748 Garching bei München
 Tel. +49 7152 203 6440
 Fax +49 7152 203 77050
 muenchen.de@geze.com

GEZE GmbH
 Niederlassung Ost
 Albert-Einstein-Ring 5
 14532 Kleinmachnow bei Berlin
 Tel. +49 7152 203 6840
 Fax +49 7152 203 76849
 berlin.de@geze.com

GEZE GmbH
 Niederlassung Mitte/Luxemburg
 Adenauerallee 2
 61440 Oberursel (b. Frankfurt)
 Tel. +49 7152 203 6888
 Fax +49 7152 203 6891
 frankfurt.de@geze.com

GEZE GmbH
 Niederlassung West
 Heltorfer Straße 12
 40472 Düsseldorf
 Tel. +49 7152 203 6770
 Fax +49 7152 203 76770
 duesseldorf.de@geze.com

GEZE GmbH
 Niederlassung Nord
 Haus 11, 1. OG - Theodorstr. 42-90
 22761 Hamburg-Bahrenfeld
 Tel. +49 7152 203 6600
 Fax +49 7152 203 76608
 hamburg.de@geze.com

GEZE Service GmbH
 Niederlassung Süd-West
 Reinhold-Vöster-Straße 25
 71229 Leonberg
 Tel. +49 1802 923392
 Fax +49 7152 9233 359
 service-leonberg.de@geze.com

GEZE Service GmbH
 Niederlassung Süd
 Parking 17
 85748 Garching bei München
 Tel. +49 1802 923392
 Fax +49 7152 9233 859
 service-muenchen.de@geze.com

GEZE Service GmbH
 Niederlassung Mitte
 Oberurseler Str. 69
 61440 Oberursel
 Tel. +49 1802 923392
 Fax +49 7152 9233 659
 service-oberursel.de@geze.com

GEZE Service GmbH
 Niederlassung West
 Heltorfer Straße 12
 40472 Düsseldorf
 Tel. +49 1802 923392
 Fax +49 7152 9233 559
 service-duesseldorf.de@geze.com

GEZE Service GmbH
 Niederlassung Ost
 Albert-Einstein-Ring 5
 14532 Kleinmachnow bei Berlin
 Tel. +49 1802 923392
 Fax +49 7152 9233 759
 service-berlin.de@geze.com

GEZE Service GmbH
 Niederlassung Nord
 Theodorstr. 42-90, Haus 11
 22761 Hamburg
 Tel. +49 1802 923392
 Fax +49 7152 9233 459
 service-hamburg.de@geze.com

Austria
 GEZE Austria
 Wiener Bundesstrasse 85
 A-5300 Hallwang
 Tel: +43 6225 87180
 Fax: +43 6225 87180 299
 austria.at@geze.com

**Baltic States –
 Lithuania / Latvia / Estonia**
 Tel. +371 678960 35
 baltic-states@geze.com

Benelux
 GEZE Benelux B.V.
 Industrieterrein Kapelbeemd
 Steenoven 36
 5626 DK Eindhoven
 Tel. +31 4026290 80
 Fax +31 4026290 85
 benelux.nl@geze.com

Bulgaria
 GEZE Bulgaria - Trade
 Representative Office
 Nickolay Haitov 34 str., fl. 1
 1172 Sofia
 Tel. +359 247043 73
 Fax +359 247062 62
 office-bulgaria@geze.com

China
 GEZE Industries (Tianjin) Co., Ltd.
 Shuangchenzhong Road
 Beichen Economic Development
 Area (BEDA)
 Tianjin 300400, P.R. China
 Tel. +86 22 26973995
 Fax +86 22 26972702
 chinasales@geze.com.cn

GEZE Industries (Tianjin) Co., Ltd.
 Branch Office Shanghai
 Jia Little Exhibition Center
 Room C 2-102
 Shenzhuan Rd. 6000
 201619 Shanghai, P.R. China
 Tel. +86 21 52340960
 Fax +86 21 64472007
 chinasales@geze.com.cn

GEZE Industries (Tianjin) Co., Ltd.
 Branch Office Guangzhou
 Room 17 C 3
 Everbright Bank Building, No.689
 Tian He Bei Road
 510630 Guangzhou, P.R. China
 Tel. +86 20 38731842
 Fax +86 20 38731834
 chinasales@geze.com.cn

GEZE Industries (Tianjin) Co., Ltd
 Branch Office Beijing
 Room 04-05, 7th Floor
 Red Sandalwood Plaza
 No. 27 Jianguo Road
 Chaoyang District
 100024 Beijing, P.R.China
 Tel. +86 10 85756009
 Fax +86 10 85758079
 chinasales@geze.com.cn

France
 GEZE France S.A.R.L.
 ZAC de l'Orme Rond
 RN 19
 77170 Servon
 Tel. +33 1 606260 70
 Fax +33 1 606260 71
 france.fr@geze.com

Hungary
 GEZE Hungary Kft.
 Hungary-2051 Biatorbágy
 Vendel Park
 Huber u. 1.
 Tel. +36 23532 735
 Fax +36 23532 738
 office-hungary@geze.com

Iberia
 GEZE Iberia S.R.L.
 C/ Andorra 24
 08830 Sant Boi de Llobregat
 (Barcelona)
 Tel. +34 902194 036
 Fax +34 902194 035
 info@geze.es

India
 GEZE India Private Ltd.
 MF 2 & 3, Guindy Industrial Estate
 Ekkattuthangal
 Chennai 600 097
 Tamilnadu
 Tel. +91 44 406169 00
 Fax +91 44 406169 01
 office-india@geze.com

Italy
 GEZE Italia S.r.l
 Sede di Vimercate
 Via Fiorbellina 20
 20871 Vimercate (MB)
 Tel. +39 0399530401
 Fax+39 039 9530459/419
 italia.it@geze.com

Sede di Roma
 Via Lucrezia Romana, 91
 00178 Roma
 Tel. +39 06 726531 1
 Fax +39 06 726531 36
 roma@geze.biz

Poland
 GEZE Polska Sp.z o.o.
 ul. Marywilska 24
 03-228 Warszawa
 Tel. +48 224 404 440
 Fax +48 224 404 400
 geze.pl@geze.com

Romania
 GEZE Romania S.R.L.
 IRIDE Business Park,
 Str. Dimitrie Pompeiu nr. 9-9a,
 Building 10, Level 2, Sector 2,
 020335 Bucharest
 Tel.: +40 212507 750
 Fax: +40 316201 258
 office-romania@geze.com

Russia
 OOO GEZE RUS
 Gamsonovskiy Per. 2
 115191 Moscow
 Tel. +7 495 93306 59
 Fax +7 495 93306 74
 office-russia@geze.com

Scandinavia – Sweden
 GEZE Scandinavia AB
 Mallslingan 10
 Box 7060
 18711 Täby, Sweden
 Tel. +46 87323 400
 Fax +46 87323 499
 sverige.se@geze.com

Scandinavia – Norway
 GEZE Scandinavia AB avd. Norge
 Industriveien 34 B
 2073 Dal
 Tel. +47 63957 200
 Fax +47 63957 173
 norge.se@geze.com

Scandinavia – Denmark
 GEZE Danmark
 Branch office of GEZE Scandinavia AB
 Mårkærvej 13 J-K
 2630 Taastrup
 Tel. +45 463233 24
 Fax +45 463233 26
 danmark.se@geze.com

Singapore
 GEZE (Asia Pacific) Pte. Ltd.
 21 Bukit Batok Crescent
 #23-75 Wcega Tower
 Singapore 658065
 Tel: +65 6846 1338
 Fax: +65 6846 9353
 gezesea@geze.com.sg

South Africa
 Geze South Africa (Pty) Ltd.
 GEZE, Building 3, 1019 Morkels Close
 Midrand 1685
 Tel: +87 94337 88
 Fax: +86 66137 52
 info@gezesa.co.za

Switzerland
 GEZE Schweiz AG
 Zeliglimatte 1A
 6260 Reiden
 Tel. +41 62 28554 00
 Fax +41 62 28554 01
 schweiz.ch@geze.com

Turkey
 GEZE Kapı ve Pencere Sistemleri
 San. ve Tic. Ltd. Sti.
 İstanbul Anadolu Yakası Organize
 Sanayi Bölgesi
 Gazi Bulvarı Caddesi 8.Sokak No:8
 Tuzla-İstanbul
 Tel. +90 216 45543 15
 Fax +90 216 45582 15
 office-turkey@geze.com

Ukraine
 LLC GEZE Ukraine
 ul. Viskoznaya, 17,
 Building 93-B, Office 12
 02660 Kiev
 Tel./Fax +38 445012225
 office-ukraine@geze.com

United Arab Emirates/GCC
 GEZE Middle East
 P.O. Box 17903
 Jebel Ali Free Zone
 Dubai
 Tel. +971 48833 112
 Fax +971 48833 240
 gezeme@geze.com

United Kingdom
 GEZE UK Ltd.
 Blenheim Way
 Fradley Park
 Lichfield
 Staffordshire WS13 8SY
 Tel. +44 15434430 00
 Fax +44 15434430 01
 info.uk@geze.com

GEZE REPRESENTATIVE